

AG-2010 Preamplifier

The AG-2010 preamplifier offers a similar mix of performance and features as the AH-2010 preamplifier, except that the gain is designed to compensate for frequency variation observed in the HGL-0200 and HGL-0085 hydrophones between 20 and 40 MHz. The combined solution enables the flattest response with a sensitivity that varies less than +/- 3 dB from 0.25 to 40 MHz, which is desirable for accurate measurement of typical pulsed diagnostic ultrasound systems.

Features

- Designed to electronically match the HGL-0200 and HGL-0085
- Flat frequency response when combined with the HGL
- Low noise for > 78 dB dynamic range
- Fully submersible
- Only one cable in the tank
- Waterproof mating to Onda hydrophones
- Overload protection

Technical Specifications

- Voltage Gain: 20 dB
- Bandwidth: 50 kHz - 60 MHz
- Input Impedance: 1 M Ω in parallel with 7 pF
- Output Impedance: 50 Ω
- Max Output into 50 Ω : 4 Vpp below 50 MHz, 1 Vpp above 50 MHz
- Power Consumption (max): 2 W

A Precision Gain and Input Capacitance calibration certificate is provided with each device.

Specifications are subject to change without notice.



AG-2010 Preamplifier




AG-2010 preamplifier with HGL-0200 hydrophone



Amplifier is supplied in a kit with Universal Power Supply, DC Block, 1m coaxial cable and calibration certificate.

Typical Gain Plots



Mechanical Specifications

Weight: 36 g
Material: Hermetically sealed stainless steel body.

